

| Unit | Item Description   | Quantity |  | ABC       |
|------|--|----------|--|-----------|
| Unit | <b>Printer</b><br><b>Operational Panel:</b> 2-Line LCD<br><b>Consumptio:</b> 290 W (Printing) / 60 W (Ready) / 1.8 W (Power Save)<br><b>Weight:</b> 14.06 kg (31 lb)<br><b>Value Added Functions:</b> NFC, Mobile Print, WPS<br><b>Memory (Standard):</b> 128 MB<br><b>Noise Level:</b> Less than 46 dBA (Colour Printing), Less than 48 dBA (Mono Printing) / Less than 52 dBA (Copying) / Less than 53 dBA (ADF)<br><b>Max. Monthly Duty Cycle:</b> 20000 Pages<br><b>Processor:</b> 800 MHz<br><b>Interface (Standard):</b> Hi-Speed USB 2.0 / 10 / 100 Base Tx / Wireless 802.11b/g/n<br><b>Dimension (WxDxH):</b> 406 x 362 x 333.5 mm (16" x 14.3" x 13.1") (except paper tray)<br><b>Speed (Mono):</b> Up to 18 ppm in A4 (19 ppm in Letter)<br><b>First Print Out Time (Colour):</b> Less than 26 seconds (From Ready Mode)<br><b>Duplex Print:</b> Manual<br><b>Speed (Colour):</b> Up to 4 ppm in A4 (4 ppm in Letter)<br><b>Resolution:</b> Up to 2400 x 600 dpi effective output (600 x 600 x 2 bit)<br><b>Client OS Support:</b><br>Windows 10 / 8 / 7 / Vista / XP / 2008R2 / 2008 / 2003, Mac OS X 10.6 - 10.10, Various Linux<br><i>(or at least equivalent)</i> | 3        |  | 75,000.00 |
|      |  |          |  |           |
| Unit | <b>Scanner</b><br><b>Type:</b> USB Powered Sheetfed Scanner<br><b>Scanning sensor unit:</b> CMOS CIS 1 Line Sensor<br><b>Optical resolution:</b> 600dpi<br><b>Light source:</b> RGB LED<br><b>Scanning side:</b> Front / Back / Duplex<br><b>Interface:</b> Hi speed USB 2.0 & USB 3.0<br><b>Dimensions (WxDxH):</b> Tray Closed: 285 (W) x 95 (D) x 40 (H)mm<br>Tray Opened: 285 (W) x 257 (D) x 174 (H)mm<br><b>Weight:</b> Approx. 1.0kg<br><b>Power requirements:</b> USB 2.0 bus power: 0.5A (1.0A in combination with power supply USB cable)<br>USB 3.0 bus power: 0.9A<br>Optional AC Adaptor DC6V. 0.8A<br><b>Power consumption:</b> USB cable only: 2.5W (USB 2.0), 4.5W (USB 3.0)<br>USB cable and power supply USB cable: 5.0W (USB 2.0), 7.0W (USB 3.0)<br>Sleep mode: 1.5W, Power OFF: 0.1W<br><b>Operating environment:</b> 10 – 32.5°C (50 – 90.5°F), Humidity: 25 – 80% RH<br><b>Environmental compliance:</b> RoHS and ENERGY STAR<br><i>(or at least equivalent)</i>  | 2        |  | 20,000.00 |
|      |  |          |  |           |
| Unit | <b>Switch</b><br><b>Standards and Protocols:</b><br>803.3 10Base-T ethernet<br>802.3u 100Base-TX Fast Ethernet<br>802.3ab 100Base-T Gigabit Ethernet<br>802.3z Gigabit Ethernet<br>802.3x flow control<br>802.1p Priority<br>802.3az, Energy Efficient Ethernet<br><b>Ports:</b> 24-ports compact Gigabit Switch<br><b>LED Indicators:</b> System/PWR, Link / Activity<br><b>Power:</b> 100-240 VAC, 50-60 Hz, Internal, Universal<br><i>(or at least equivalent)</i>  | 5        |  | 80,000.00 |
|      |  |          |  |           |

\*\*\* Nothings Follow \*\*\*

Total:

175,000.00